

WrapidCoat® PE

Superior Mechanical Protection

WrapidCoat® PE is tough, polyethylene based tape with special high tack adhesive formulated to aid corrosion resistance of metal piping systems and provides mechanical protection for WrapidBond® coated pipe. The high tack adhesive and tough backing provides an effective barrier to water and oxygen which provides effective corrosion protection and soil stress resistance.

Chemical Resistance

- The product is resistant to corrosive salt water, soil acids, alkalies and salts, common chemicals, chemical vapors, and short term exposure to outdoor weathering and sunlight.

Flexibility & Adhesion

- WrapidCoat® PE is a highly conformable, 0.50 mm (20 mil) thick tape designed for application over a wide temperature range. Very easy to apply at high or low temperatures it provides excellent adhesion and shear resistance.

Superior Mechanical Protection

- WrapidCoat® PE is a medium density polyethylene film, with a butyl rubber adhesive applied. The product is designed to provide excellent mechanical protection for pipeline coating systems.

Long Term Corrosion Protection

- In combination with WrapidBond®, the composition of the product is such that it provides an effective barrier to water and oxygen which provides effective corrosion protection in onshore and offshore environments.



Applications



Oil & Gas



Repair & Rehab



Corrosion Coating



Girth-Weld Joints



Fittings & Bends



WrapidBond® inner wrap

WrapidCoat® PE outer wrap

WrapidCoat® PE

Superior Mechanical Protection

Typical Product Properties	Test Method	WrapidCoat® PE
Color		Black or White
Thickness		0.50 mm (20 mils)
Elongation @ Break	ASTM D1000	200%
Tensile Strength	ASTM D1000	70.0 N/cm (40 pli)
Impact Strength	ASTM G14	15 J
Adhesion to Backing @ 23°C (74°F)	ASTM D1000	5.6 N/cm (3.1 pli)
Normal Application Temperature Range		-34°C to 71°C (-30°F to 160°F)
Normal Service Temperature Range		-34°C to 85°C (-30°F to 185°F)

* This data is not to be used for specification. Values listed are for typical properties and should not be considered minimum or maximum. Refer to the WrapidBond® Product Data Sheet for ordering information.

The product information shown here is intended as a guide for standard products.

Consult your Canusa representative for specific projects or unique applications at info@canusacps.com.



Western Hemisphere

SFL Canusa - WH
4757 93rd Ave NW
Edmonton, Alberta T6B 2T6
Canada

Tel: +1 587-754-8701

Europe

SealForLife Industries
Nijverheidsstraat 13
B-2260 Westerlo
Belgium

Middle East

SFL Canusa Middle East PPTS LLC
KLP5, Block B, Unit B-01,
Sector no.: KHIA8, Al Ma'mourah
PO Box 2621, Abu Dhabi,
The United Arab Emirates

**Quality Management
system registered to
ISO 9001**

Since 1967, Canusa-CPS has been a leading developer and manufacturer of specialty pipeline coatings for the sealing and corrosion protection of pipeline joints and other substrates. Canusa-CPS high performance products are manufactured to the highest quality standards and are available in a number of configurations to accommodate many specific project applications.

Canusa warrants that the product conforms to its chemical and physical description and is appropriate for the use stated on the product data sheet when used in compliance with Canusa's written instructions. Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith. Canusa's liability is stated in the standard terms and conditions of sale. Canusa makes no other warranty either expressed or implied. All information contained in this data sheet is to be used as a guide and is subject to change without notice. This data sheet supersedes all previous data sheets on this product. E&OE

PDS_Wrapid Coat PE_rev014