

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 09/08/2021

Revision date: 09/08/2021

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : CF-8 & VF-3 Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Adhesive.

1.3. Details of the supplier of the safety data sheet

Manufacturer
CANUSA-CPS

455 W Airport Rd,
Huntsville, ON P1H 1Y7
Telephone: 1-705-789-1787

1.4. Emergency telephone number

Emergency number : 613-996-6666 (Canutec) only for transport emergency
ChemTel (Contract Number MIS9425100): 1-800-255-3924

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Repr. 2

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS08

Signal word (GHS) : Warning
Hazard statements (GHS) : Suspected of damaging fertility or the unborn child.
Precautionary statements (GHS) : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS-No.) 64742-52-5	1 – 10
Talc	(CAS-No.) 14807-96-6	3 – 7
Magnesite (Mg(CO ₃))	(CAS-No.) 13717-00-5	3 – 7
2,2'-Methylenebis(4-methyl-6-tert-butylphenol)	(CAS-No.) 119-47-1	0.1 – 1
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	0.1 – 1
Disodium carbonate	(CAS-No.) 497-19-8	0.1 – 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
- Chronic symptoms : Suspected of damaging fertility or the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂). Dry chemical powder. For large fire: Water spray. Foam.
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Formaldehyde. Aldehydes. toxic and corrosive vapours.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Handle and open container with care.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Store locked up. Store tightly closed in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CF-8 & VF-3 Adhesive	
No additional information available	
Talc (14807-96-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Not Classifiable as a Human Carcinogen containing no asbestos fibers
USA - OSHA - Occupational Exposure Limits	
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
OSHA PEL TWA [2]	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	1000 mg/m ³ (containing no asbestos and <1% quartz)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
Magnesite (Mg(CO₃)) (13717-00-5)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
2,2'-Methylenebis(4-methyl-6-tert-butylphenol) (119-47-1)	
No additional information available	
Magnesium oxide (MgO) (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	15 mg/m ³ (fume, total particulate)

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

USA - IDLH - Occupational Exposure Limits	
IDLH	750 mg/m ³ (fume)
Disodium carbonate (497-19-8)	
No additional information available	
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
No additional information available	

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves resistant to chemical penetration. Natural rubber gloves. Nitrile rubber gloves. Butyl rubber gloves. Neoprene rubber gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Not applicable
Colour	: Not applicable
Odour	: Not applicable
Odour threshold	: Not applicable
pH	: Not applicable
Melting point	: Not applicable
Freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: Not applicable
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: Not applicable
Relative vapour density at 20 °C	: Not applicable
Relative density	: 0.97
Solubility	: Not applicable
Partition coefficient n-octanol/water	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not applicable
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosive limits	: Not applicable
Explosive properties	: Not applicable
Oxidising properties	: Not applicable

9.2. Other information

Softening point	: 90 °C (194 °F)
-----------------	------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Formaldehyde. Aldehydes. Hydrocarbons. methane. Propane. butene isomers. dimethylpropane isomers. dimethylheptane isomers. Formic acid. Acetone. Peroxides may be formed on prolonged contact with air. Toxic and corrosive vapours may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not applicable
Acute toxicity (dermal) : Not applicable
Acute toxicity (inhalation) : Not applicable

Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

2,2'-Methylenebis(4-methyl-6-tert-butylphenol) (119-47-1)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

Magnesium oxide (MgO) (1309-48-4)	
LD50 oral rat	3870 mg/kg

Disodium carbonate (497-19-8)	
LD50 oral rat	4090 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:EPA 16 CFR 1500.40
LC50 inhalation rat	2300 mg/m ³ (Exposure time: 2 h)

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation : Not applicable
Serious eye damage/irritation : Not applicable
Respiratory or skin sensitisation : Not applicable
Germ cell mutagenicity : Not applicable
Carcinogenicity : Not applicable

Talc (14807-96-6)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

2,2'-Methylenebis(4-methyl-6-tert-butylphenol) (119-47-1)	
NOAEL (chronic, oral, animal/male, 2 years)	12.7 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	15.1 mg/kg bodyweight Animal: rat, Animal sex: female, Remarks on results: other:Effect type: toxicity (migrated information)

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : Not applicable
STOT-repeated exposure : Not applicable

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Talc (14807-96-6)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard	: Not applicable
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Talc (14807-96-6)	
LC50 - Fish [1]	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'

2,2'-Methylenebis(4-methyl-6-tert-butylphenol) (119-47-1)	
EC50 - Crustacea [1]	> 4.8 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	0.89 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.34 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Disodium carbonate (497-19-8)	
LC50 - Fish [1]	300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 - Crustacea [1]	265 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	310 – 1220 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	200 – 227 mg/l Test organisms (species): Ceriodaphnia sp.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

CF-8 & VF-3 Adhesive	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

CF-8 & VF-3 Adhesive	
Bioaccumulative potential	Not established.
Talc (14807-96-6)	
BCF - Fish [1]	(no known bioaccumulation)
Disodium carbonate (497-19-8)	
BCF - Fish [1]	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

CF-8 & VF-3 Adhesive

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Magnesite (Mg(CO ₃))	CAS-No. 13717-00-5
Chlorite-group minerals	CAS-No. 1318-59-8

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:

Magnesite (Mg(CO ₃))	CAS-No. 13717-00-5
Chlorite-group minerals	CAS-No. 1318-59-8

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Revision date : 09/08/2021
Other information : None.
Prepared by : Nexreg Compliance Inc.
For more information contact
Canusa-CPS



SDS HazCom 2012 - WHMIS 2015 (NexReg_Canusa)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.