# **SAFETY DATA SHEET**



Canusa Liquid Epoxy Types P, P-HB - Base

# **Section 1. Identification**

Product identifier : Canusa Liquid Epoxy Types P, P-HB - Base

Product code : Not available.

Other means of : Not available.

identification

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial application of coatings and inks by other than spraying	
Uses advised against	Reason
Consumer	Product is not intended for consumer use.

Supplier's details : SFL Canusa Canada Ltd., 455 West Airport Road, Huntsville, ON, P1H 1Y7,

Canada, Tel.: (+1) 705-789-1787

Seal For Life India Private Ltd., Plot17, GIDC Savli, Vadodara, Gujarat, Baroda,

India - 391775, Tel.: +91 266 726 4721

SFL Canusa Middle East Pipeline Products Trading and Services LLC, Address: Plot # 37-WR43, Sector no.: ICAD III, Musaffah South, Abu Dhabi, United Arab

Emirates, Tel: +971 2 204 9800

Seal For Life Industries, 10010 Cypress Creek Parkway Houston, TX 77070, USA,

Tel.: +1 713-999-5090

Distributor / Importer :

Emergency telephone number (with hours of

operation)

: +1 705-789-1787 (CA: 8:00 - 17:00) +91 266 726 4721 (IN: 08:00 - 17:00) +971 2 204 9800 (UAE: 08:00 - 17:00) +1 713-999-5090 (US: 8:00-17:00)

For emergencies only, call CHEMTREC (24 hours): In USA / Canada 1-800-424-9300; Outside USA +1 703-741-5970

# Section 2. Hazard identification

Classification of the substance or mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

**GHS label elements** 

Hazard pictograms :



Signal word : Warning

**Hazard statements**: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

**Precautionary statements** 

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 1/13

# Section 2. Hazard identification

#### **Prevention**

: Wear protective gloves: > 8 hours (breakthrough time): Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.< 1 hour (breakthrough time): Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.. Wear eye or face protection: Recommended: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

### Response

Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage** 

: Not applicable.

**Disposal** 

Dispose of contents and container in accordance with all local, regional, national and international regulations.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

Phenol, polymer with formaldehyde, glycidyl ether  Phenol, polymer with formaldehyde, oxiranylmethyl ether; phenol-formaldehyde polymer glycidyl ether; Etherification products of glycidyl group of (polymer of formaldehyde / phenol); Glycidyl ether modification products with epichlorohydrin or 2-methylepichlorohydrin of {polycondensation products of [ (polycondensation products of [ (polycondensation products of phenol / formaldehyde); Etherification products of oxiran-2-ylmethyl group of (polymer of formaldehyde); Etherification products of oxiran-2-ylmethyl group of (polymer of formaldehyde) phenol); Phenol polymer with formaldehyde, glycidyl ether; GLYCIDYL EPOXY NOVALAC RESIN; PHENOL, NOVOLAC RESIN; PHENOL, NOVOLAC TYPE EPOXY RESIN; POLYMER OF EPICHLOROHYDRIN AND PHENOL-FORMALDEHYDE; POLYMER, PHENOL FORMALDEHYDE WITH GLYCIDYL ETHER; Phenol,polymer with formaldehyde glycidyl ether  Epichlorhydrin-bisphenol A resin  Epichlorhydrin-bisphenol A resin  Epichlorhydrin-bisphenol A resin  Epichlorhydrin-bisphenol A pesin epoxy resin; 4,4'-   Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane; Phenol, 4,4'-   Isopropylidenediphenol, a,4'-   Isopropylidenediphenol, a,4'-   Isopropylidenediphenol, a,4'-   Isopropylidenediphenol, a,4'-   Isopropylidenediphenol, a,4'-   Isopropylidenediphenol, a,4'-   Isopropylidenediphenol, a,4'-	Ingredient name	Synonyms	% (w/w)	CAS number
Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane; Phenol, 4,4'-		oxiranylmethyl ether; phenol- formaldehyde polymer glycidyl ether; Etherification products of glycidyl group of (polymer of formaldehyde / phenol); Glycidyl ether modiification products with epichlorohydrin or 2-methylepichlorohydrin of {polycondensation products of [ (polycondensation products of phenol / formaldehyde) or alkyl(C1-9) phenol] / formaldehyde}; Etherification products of oxiran- 2-ylmethyl group of (polymer of formaldehyde / phenol); Phenol polymer with formaldehyde, glycidyl ether; GLYCIDYL EPOXY NOVALAC RESIN; PHENOL, NOVOLAC TYPE EPOXY RESIN; POLYMER OF EPICHLOROHYDRIN AND PHENOL-FORMALDEHYDE; POLYMER, PHENOL FORMALDEHYDE WITH GLYCIDYL ETHER; Phenol,polymer with	≥30 - ≤60	28064-14-4
(1-metriyletriylidene)bis-, polymer	Epichlorhydrin-bisphenol A resin	Isopropylidenediphenol, oligomeric reaction products with 1-chloro-	≥0.1 - ≤1	25068-38-6

# Section 3. Composition/information on ingredients

with 2-(chloromethyl)oxirane; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane; phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane; oxirane, (chloromethyl)-, polymer with 4,4'-(1-methylethylidene)bis [phenol]; Bisphenol A, epichlorohydrin polymer;

Epichlorohydrin, bisphenol A resin; poly{(4,4'-propane-2,2-diyldiphenol)co-[2-(chloromethyl)oxirane]}; BADGE; DGEBPA; diglycidyl ether of bis¬phenol A; bisphenol A diglycidyl ether resin; (bisphenol A)-

epichloridrin copolymer; poly[4,4'-(1-methylethylidene)bisphenol-co-

(chloromethyl)oxirane]

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-aid measures

#### Description of necessary first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the

person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Skin contact Wash contaminated clothing thoroughly with water before removing it, or wear

gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before

reuse. Clean shoes thoroughly before reuse.

: Wash out mouth with water. Remove dentures if any. If material has been Ingestion

> swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

# Potential acute health effects

: Causes serious eye irritation. Eye contact

: No known significant effects or critical hazards. Inhalation

: Causes skin irritation. May cause an allergic skin reaction. Skin contact

Ingestion : No known significant effects or critical hazards.

Date of issue/Date of revision : 4/26/2023 : 4/26/2023 Version: 2.03 3/13 Date of previous issue

# Section 4. First-aid measures

### Over-exposure signs/symptoms

: Adverse symptoms may include the following: Eye contact

pain or irritation watering redness

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

> irritation redness

: No specific data. Ingestion

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

halogenated compounds metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision : 4/26/2023 : 4/26/2023 4/13 Version : 2 03 Date of previous issue

# Section 6. Accidental release measures

### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

#### Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### Control parameters

Occupational exposure limits

None.

#### **Biological exposure indices**

No exposure indices known.

### Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision : 4/26/2023 : 4/26/2023 Version : 2 03 5/13 Date of previous issue

# Section 8. Exposure controls/personal protection

### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

# Skin protection

### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

< 1 hour (breakthrough time): Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Not necessary if room is well-ventilated. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.

Color : Black. [Dark]

Odor : Hydrocarbon. [Slight]

Odor threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 6/13

# Section 9. Physical and chemical properties and safety characteristics

Boiling point, initial boiling point, and boiling range

: Not available.

Flash point :

	Closed cup			Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method
Phenol, polymer with formaldehyde, glycidyl ether				93.4	200.1	
Distillates (petroleum), hydrotreated heavy naphthenic				98 to 344	208.4 to 651.2	EN ISO 2719
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	>93	>199.4	EU A.9			
KV - Disparlon 6500				265	509	

**Flammability** 

: Not available.

Lower and upper explosion

: Not available.

limit/flammability limit

Not applicable.

Vapor pressure Relative vapor density

: Not available.

Relative density

: 1.5

Solubility in water

: Not applicable.

Miscible with water

No.

Partition coefficient: n-

. 110.

octanol/water

: Not applicable.

Auto-ignition temperature

: Not applicable.

**Decomposition temperature** 

: Not available.

Viscosity

: Not available.

**Particle characteristics** 

Median particle size : Not applicable.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 7/13

# Section 11. Toxicological information

# Information on toxicological effects

# **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Epichlorhydrin-bisphenol A resin	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Female	>2000 mg/kg	-

# **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Epichlorhydrin-bisphenol A resin	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 uL	-
	Skin - Severe irritant	Rabbit		24 hours 2 mg	-

# **Sensitization**

	Route of exposure	Species	Result
Epichlorhydrin-bisphenol A resin	skin	Mouse	Sensitizing

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Epichlorhydrin-bisphenol A resin	-	Experiment: In vitro Subject: Bacteria	Positive
	-	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Positive
	-	Experiment: In vivo Subject: Mammalian-Animal Cell: Germ	Negative

# **Carcinogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Epichlorhydrin-bisphenol A resin	Negative - Dermal - TC	Mouse - Female	0.1 mg/kg	2 years; 3 days per week
	Negative - Dermal - TC	Rat - Female	1 mg/kg	2 years; 5 days per week
	Negative - Oral - TC	Rat - Male, Female	15 mg/kg	2 years; 7 days per week

# **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Epichlorhydrin-bisphenol A resin	Negative	Negative	Negative	Rat - Male, Female	Oral	-

# **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Epichlorhydrin-bisphenol A resin	Negative - Dermal	Rabbit - Female	-	-
	Negative - Oral Negative - Oral	Rabbit - Female Rat - Female	-	-

# **Specific target organ toxicity (single exposure)**

Not available.

# Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 8/13

# Section 11. Toxicological information

Not available.

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

### Potential acute health effects

**Eye contact**: Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Epichlorhydrin-bisphenol A resin	Sub-chronic NOAEL Dermal	Rat - Male, Female	10 mg/kg	-
	Sub-chronic NOAEL Oral	Rat - Male, Female	50 mg/kg	-

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Reproductive toxicity: No known significant effects or critical hazards.

### **Numerical measures of toxicity**

Acute toxicity estimates

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 9/13

# Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	 Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/l)
Canusa Liquid Epoxy Types P, P-HB - Base Epichlorhydrin-bisphenol A resin	6642.5 2500	 	N/A N/A	N/A N/A

# Section 12. Ecological information

# **Toxicity**

Product/ingredient name	Result	Species	Exposure
Epichlorhydrin-bisphenol A resin	Acute EC50 11 mg/l Fresh water	Aquatic plants	72 hours
	Acute EC50 1.8 mg/l Fresh water Acute LC50 2 mg/l Acute NOEC 4.2 mg/l Fresh water Chronic NOEC 0.3 mg/l Fresh water	Daphnia Fish Aquatic plants Daphnia	48 hours 96 hours 72 hours 21 hours

### Persistence and degradability

r crosscrice and degradability					
Product/ingredient name	Test	Result		Dose	Inoculum
Epichlorhydrin-bisphenol A resin	OECD 301F 301F Ready Biodegradability - Manometric Respirometry Test	5 % - Not readily - 2	28 days	-	Activated sludge
Product/ingredient name	Aquatic half-life		Photolysi	S	Biodegradability
Epichlorhydrin-bisphenol A resin	Fresh water 4.83 days, pH 4, 25°C (OECD Test Guideline 111) Fresh water 7.1 days, pH 9, 25°C (OECD Test Guideline 111) Fresh water 3.58 days, pH 7, 25°C (OECD Test Guideline 111)		-		Not readily

# **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Epichlorhydrin-bisphenol A resin	2.64 to 3.78	31	low

# **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 10/13

# Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	TDG Classification	DOT Classification	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.

#### **Additional information**

**TDG Classification** 

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.

**Explosive Limit and Limited Quantity Index** 5 **Special provisions** 16, 99

**DOT Classification** 

: Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

Limited quantity Yes.

Packaging instruction Exceptions: 155. Non-bulk: 203. Bulk: 241.

**Special provisions** 8, 146, 173, 335, IB3, T4, TP1, TP29

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Emergency schedules F-A, S-F Special provisions 274, 335, 969

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 11/13

# Section 14. Transport information

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1,

5.0.2.6.1.1 and 5.0.2.8.

**Quantity limitation** Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities -

Passenger Aircraft: 30 kg. Packaging instructions: Y964.

**Special provisions** A97, A158, A197, A215

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

# Section 15. Regulatory information

### **Canadian lists**

Canadian NPRI : None of the components are listed. : None of the components are listed. CEPA Toxic substances

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

### **Inventory list**

**Australia** : Not determined. Canada Not determined. China : Not determined.

**Eurasian Economic Union** : Russian Federation inventory: Not determined.

: Japan inventory (CSCL): Not determined. **Japan** 

Japan inventory (ISHL): Not determined.

: Not determined. **New Zealand** : Not determined. **Philippines** Republic of Korea : Not determined. : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. **Turkey** : Not determined. **United States** : Not determined. **Viet Nam** 

Date of issue/Date of revision : 4/26/2023 : 4/26/2023 12/13 Date of previous issue Version : 2 03

# Section 16. Other information

### **History**

Date of printing : 4/26/2023 Date of issue/Date of : 4/26/2023

revision

Date of previous issue : 4/26/2023

Version : 2.03

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HPR = Hazardous Products Regulations IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

### Procedure used to derive the classification

Classification	Justification
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method

References : Not available.

✓ Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 4/26/2023 Date of previous issue : 4/26/2023 Version : 2.03 13/13